

CWSO



Performance features

- » Acoustic alarm device
- » Optimised for use with D+H SHEV control panels
- » VdS approval

Type	Art. No.	Description	Technical data													
CWSO-RR-S1	30.301.55	Signal emitter » 32 different sounds can be programmed » Acoustic signal emitter in accordance with EN 54-3 » VdS approval number: G 215015 » Optional connection for activating a second sound » Synchronous sound output » Volume can be set in 2 levels on the device	<table><tr><td>Supply</td><td>9 ... 29 V DC / 0.03 A</td></tr><tr><td>Loudness</td><td>102.1 dB</td></tr><tr><td>Type of protection</td><td>IP 21C</td></tr><tr><td>Colour</td><td>Red (~ RAL 3020)</td></tr><tr><td>Diameter</td><td>100 mm</td></tr><tr><td>Weight</td><td>0.19 kg</td></tr></table>	Supply	9 ... 29 V DC / 0.03 A	Loudness	102.1 dB	Type of protection	IP 21C	Colour	Red (~ RAL 3020)	Diameter	100 mm	Weight	0.19 kg	
Supply	9 ... 29 V DC / 0.03 A															
Loudness	102.1 dB															
Type of protection	IP 21C															
Colour	Red (~ RAL 3020)															
Diameter	100 mm															
Weight	0.19 kg															

